

10. Suzanne Muyshondt and Tony Visconsi

61 Buckingham Rd

Variance: To construct a detached garage with a side setback of 2'-2" vs the 5' that is permitted. Per Schedule: 1153.15 (1).

Variance: To construct a detached garage with a rear setback of 3'-1" vs the 5' that is permitted. Per Schedule: 1153.15 (1).

Schedule 1153.15				
Permitted Accessory Structures in Front, Side and Rear Yards				
Use	Yard Permitted	Minimum Setback From Lot Line		
		Front	Side	Rear
(1) Detached accessory buildings, including garages	Rear	NP	5 ft.	5 ft.

Variance: To construct a new single-family house with an attached porte-cochere that has a side setback of 4'-9" vs the 8' that is permitted. Per Schedule: 1153.07 (1)A.

Variance: To construct a new single-family home with an egress window that has a 5' side setback vs the 8' that is permitted. 1153.07 (1)A.

Schedule 1153.07		
Minimum Setback Requirements		
	R-1 Single-Family Residential District	R-2 Two-Family Residential District
(1) Side Setback ^(a)		
A. Minimum of any one side	8 feet	8 feet
B. Total side setback	16 feet	16 feet

Variance: To install two air conditioning condensers with side setbacks of 5'-5" and 5'-9" vs the 10' that is permitted. Per Section: 1153.15 (k)(1).

1153.15 ACCESSORY USES AND STRUCTURES.

(k) Air Conditioning, Generators and Heat Pumps. Air conditioner condensers, generators and heat pumps shall comply with the following:

(1) Outdoor condensers and heat pumps may be located in either the rear yard or the side yard, but shall not be located less than ten (10) feet from the side lot line. No more than two (2) such units may be located in the side yard. Such units shall be baffled so as not to exceed the noise level of seventy (70) decibels measured from the lot line, and screened with evergreen plant material so that within two (2) years the equipment is adequately screened from view.

Variance: To construct a new single-family residence with a covered front stoop that has a 26'-4" front setback vs the required 30' as shown on the setback map, City of Rocky River, May 12, 1975. Per Section: 1153.07 (a).



Variance: To construct a new single-family residence with a height of 27'-1" vs the 25' that is permitted. Per Section: 1153.09 (a).

1153.09 HEIGHT REQUIREMENTS.


All buildings and structures in any residential district shall comply with the following height regulations:

- (a) The height of principal buildings and structures shall not exceed twenty-five (25) feet.

1123.02 DEFINITIONS.

(19) Building height. The vertical distance, measured from the average elevation of the finished grade at the front of the building to the highest point of the roof for a flat roofs; to the declines of mansard roofs; and to the mean height between eaves and ridge for gable, hip and gambrel roofs. Where a building is located on sloping terrain, the height shall be measured from the average finished grade at the building walls. See Figure 1. See Section 1181.01, Supplementary Height Regulations.

Building Height



Variance: To construct a detached garage with a height of 16’ -10” vs the 15’ that is permitted. Per Section: 1153.09 (b).

1153.09 HEIGHT REQUIREMENTS.

All buildings and structures in any residential district shall comply with the following height regulations:

- (a) The height of principal buildings and structures shall not exceed twenty-five (25) feet.
- (b) The height of accessory buildings and structures shall not exceed ten (10) feet, except the height of detached garages shall not exceed twelve (12) feet at the highest point of the structure for a flat roof, and shall not exceed fifteen (15) feet at the highest point of the structure for any other roof that is not a flat roof, notwithstanding the height definition defined in Section 1123.02(b)(19) of this Code.
- (c) Permitted height exceptions are set forth in Section 1181.01, Supplementary Height Regulations. (Ord. 87-17. Passed 12-17-18.)

Variance: To construct a new single-family residence with a detached garage that has a lot coverage of 35.3% vs the 28% that is permitted. Per Schedule: 1153.05 (3).

Schedule 1153.05		
Minimum Lot Requirements		
	R-1 Single-Family Residential District	R-2 Two-Family Residential District
(1) Minimum lot area	10,000 square feet	6000 square feet (b)
(2) Minimum width at building setback line ^(a)	75 feet	60 feet
(3) Maximum lot coverage by building	28%	28%