

10. Brice Wolverton

22670 Detroit Rd

Variance: To install an accessory off-street parking space that is 16' wide vs the 8' that is permitted. Per Section: 1153.15 (I)(4)B.

Variance: To install a turnaround driveway with two curb cuts on a lot that has a front setback of 42'-6" vs two curb cuts shall be permitted for a lot with a front setback that is at least fifty (50) feet or greater. Per Section: 1153.15 (I)D.

1153.15 ACCESSORY USES AND STRUCTURES.

(I) Additional Regulations for Vehicles.

(4) Accessory off-street parking spaces located in the front yard shall adjoin the driveway between the driveway and the nearest side lot line, provided parking spaces shall not be located directly in front of the dwelling.

A. Parking areas, including driveways, for single family detached and two family dwellings shall be located not less than three (3) feet from adjoining property lines as provided in Section 1111.09(c)

B. An accessory parking space meeting the standards above shall be no wider than eight (8) feet and no longer than eighteen (18) feet long with a return to the driveway within thirty (30) feet measured from the front of the garage. Accessory parking spaces are prohibited in cases of the setback being thirty five (35) feet or less or where a three (3) car garage is proposed or exists. Refer to drawing 1153.15(I)(4)D. for clarity.

C. Accessory parking spaces in R-1 & R-2 districts will be screened between the property line and parking spaces with evergreen plant material in a manner that so that within four (4) years the vehicle is completely obscured from view.

D. Driveways shall not be less than eight (8) feet or greater than twenty (20) feet in width in R-1 and R-2 Districts except where a three (3)-car garage exists or is proposed the driveway shall not exceed thirty (32) feet in width. Where the building setback is 35' or less a full width driveway is permitted in order to service two (2) and three (3) car garages. In R-1 and R-2 Districts, only one curb cut shall be permitted for any lot, except that two curb cuts shall be permitted for any lot that meets all of the following conditions:

1. The lot width is ninety (90) feet or wider; and,
2. The front setback for the lot is at least fifty (50) feet or greater; and,
3. The proposed turn-around driveway and associated durable edging shall be no greater than twelve (12) feet in total width and,
4. For corner lots, both curb cuts are to be located on the same street.