



Symbol	Label	Image	QTY	Catalog Number	Description	Lamp	Number Lamps	Lumens per Lamp	LF	Wattage	Polar Plot
○	CL620		11	CL620 L4L20 40K	LumSTIK 6in		1	2036	1	18.7	
□	P1 Type 4		5	RSX1 LED P1 40K R4	RSX Area Fixture Size 1 P1 Lumen Package 4000K CCT Type R4 Distribution		1	7189	1	51.34	
□	P2 Type 2		1	RSX2 LED P2 40K R2	RSX Area Luminaire Size 2 P2 Lumen Package 4000K CCT Type R2 Distribution		1	17263	1	114.071	
□	P2 Type 2 HS		1	RSX2 LED P2 40K R2 HS	RSX Area Luminaire Size 2 P2 Lumen Package 4000K CCT Type R2 Distribution with HS shade		1	13052	1	114.07	
□	P2 Type 3 HS		7	RSX2 LED P2 40K R3 HS	RSX Area Luminaire Size 2 P2 Lumen Package 4000K CCT Type R3 Distribution with HS shade		1	12074	1	114.07	
□	P2 Type 4 Double		2	RSX2 LED P2 40K R4	RSX Area Fixture Size 2 P2 Lumen Package 4000K CCT Type R4 Distribution		1	17427	1	228.14	
□	WDG E1 VW		4	WDGE1 LED P1 40K 80CRI VW	WDGE1 LED WITH P1 - PERFORMANCE PACKAGE, 4000K, 80CRI, VISUAL COMFORT WIDE OPTIC		1	1229	1	10.0002	
□	WDG E2 4		2	WDGE2 LED P2 40K 80CRI T4M	WDGE2 LED WITH P2 - PERFORMANCE PACKAGE, 4000K, 80CRI, TYPE 4 MEDIUM OPTIC		1	2018	1	18.9815	
□	WDG E2 R3		3	WDGE2 LED P2 40K 80CRI T3M	WDGE2 LED WITH P2 - PERFORMANCE PACKAGE, 4000K, 80CRI, TYPE 3 MEDIUM OPTIC		1	2062	1	18.9815	
□	WDG E2 VW		4	WDGE2 LED P1 40K 80CRI VW	WDGE2 LED WITH P1 - PERFORMANCE PACKAGE, 4000K, 80CRI, VISUAL COMFORT WIDE OPTIC		1	1289	1	9.81	

Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Front Parking	✕	2.5 fc	7.0 fc	0.5 fc	14.0:1	5.0:1
North Parking	✕	2.1 fc	5.6 fc	0.4 fc	14.0:1	5.3:1
Parking Deck	✕	2.0 fc	6.1 fc	0.5 fc	12.2:1	4.0:1
Rear Parking	✕	2.1 fc	6.6 fc	0.4 fc	16.5:1	5.3:1
South Driveway	✕	4.6 fc	8.9 fc	1.5 fc	5.9:1	3.1:1
Stairs - Bottom Steps	+	1.8 fc	3.4 fc	0.6 fc	5.7:1	3.0:1
Stairs - Middle Platform	+	6.7 fc	8.3 fc	5.9 fc	1.4:1	1.1:1
Stairs - Top Platform	+	0.3 fc	0.5 fc	0.0 fc	N/A	N/A
Stairs - Top Steps	+	4.4 fc	8.0 fc	0.5 fc	16.0:1	8.8:1